

ALL THE RIGHT TOOLS:


1 SNOW BLADE
Distributed through MB Products
www.m-bco.com



2 ROTARY BROOM
Distributed through MB Products
www.m-bco.com

3 SNOW BLOWER
Distributed through Kaye Corporation
www.kayecorp.com/new

4 CATCHING SYSTEM
Heavy-duty steel frame with sturdy, lightweight aluminum catcher box with a capacity of 24 cubic feet (19.3 bushels). Conveniently dump from the seat using the left hand dumping arm. Blower and adapter kit available on the 60" and 72" deck. Blower is assembled directly to the right-hand side of the mower and powered via belt drive off the right side of the deck spindle.

5 OUT-FRONT DECK
Fully fabricated deck shell with an 11 ga. deck plate doubler and an additional 7 ga. tripler for each spindle mount area. The PTO driven deck system utilizes a hydraulic deck lift which allows the operator to raise or lower the deck from the comfort of the seat. The operator may adjust traction for varying terrain conditions using a variable hydraulic weight transfer control. The deck tilts up to 90 degrees for ease of service.



6 SOFT CAB
Manufactured by Femco
www.femcomfg.com

7 HARD CAB
Manufactured by Jodale-Perry


LIMITED WARRANTY

—TRACTOR—

2 YEAR | **1500** HOUR

—ENGINE—

3 YEAR | **2000** HOUR

See your local Hustler dealer for complete warranty details

ENGINE

MANUFACTURER	Shibaura N843L
TYPE	Liquid-cooled, inline, 3 cylinder, normally aspirated industrial diesel engine
STARTER	12-volt(1.2 kw), solenoid shift positive engagement
CHARGING SYSTEM	12-volt, 40-amp alternator
OIL FILTER	Spin-on engine oil filter 6.3qt(6.0L) oil capacity
ENGINE OIL	15W40
FUEL	Ultra-low sulphur diesel up to 5% biodiesel
FUEL CAPACITY	13 US gal(49.2L)
FUEL FILTER	Heavy-duty, spin-on fuel filter with sediment bowl
INJECTION SYSTEM	Bosch in-line, indirect injection
AIR FILTER	Heavy-duty air filter with safety filter for maximum protection, dry, dual-element
COOLING	Liquid cooled. Direct-driven, mechanical cooling fan
COOLING CAPACITY	5.6 qt (5.4 L)
GOVERNOR	Mechanical governor with 2700 RPM high idle speed
PTO	Independent type PTO. PTO speed 2209 RPM
PTO CLUTCH	Wet multi-disc manual

DRIVE SYSTEM

TYPE	Auto 4WD or Lock 4WD Hydrostatic transmission driving two-speed gear axle
FILTER	35 micron suction

GROUND SPEED	Forward Low: 0-6mph, High: 0-15mph Reverse Low: 0-4mph, High: 0-9mph
STEERING	Hydrostatic power. Tilt & telescoping steering wheel
SPEED CONTROL	2 pedals forward & reverse. 2 range hydrostatic transmission. Cruise control
BRAKES	Wet disc (single pedal control)
TIRES	Front Drive 24 x 12 - 12, turf tread Rear Drive 20 x 8 - 10
HYDRAULIC CAPACITY	8.5 gal (32 L)
WEIGHT (POWER UNIT)	1653lbs (750 Kg)

GENERAL

SAFETY FEATURES	Operator presence system connected to seat, traction pedals, PTO, and park brake switch. Hand-operated parking brake. Two-post foldable ROPS.
HEADLIGHT	Standard
SEAT SUSPENSION	Molded-vinyl, adjustable seat with armrests. Fore and aft adjustment, suspension adjustment
DECK LIFT	Hydraulic w/ adjustable weight transfer
CONTROLS	Hand-operated throttle, ignition switch, L-N-H & AWD Lock, parking brake, hydraulic lift, differential lock pedal
CUP HOLDER	Single cup holder
INDICATORS	Hour meter, temp gauge, oil pressure light, charge light, glow plug light, audible alarm for high engine temperature and low oil pressure, air filter monitor, fuel gauge

60" & 72" SIDE DISCHARGE DECK

BLADES	60": (3) 20.5" x .203" high sail 72": (3) 24.5" x .203" high sail
SPINDLES	Ductile housing, 1" diameter shaft, greaseable sealed ball bearings
BLADE TIP SPEED	60": 17,950 FPM 72": 16, 705 FPM
FRONT GAUGE TIRES	(2) - 13 x 5.0 rib tread, pneumatic
CUTTING HEIGHT	1" to 6" in .25" increments
CUTTING WIDTHS	60" & 72"
TRIM CAPACITY	60": 9.5" 72": 15.5"
TOTAL WEIGHT	60": 2,303 lbs. 72": 2,403 lbs.

72" REAR DISCHARGE DECK

BLADES	(2 LH & 1 RH) 23.9" x .203" low sail
SPINDLES	Ductile housing, 1" diameter shaft, greaseable sealed ball bearings
BLADE TIP SPEED	16,550 FPM
FRONT GAUGE TIRES	(2) - 13 x 5.0 rib tread, pneumatic
CUTTING HEIGHT	1" to 6" in .25" increments
CUTTING WIDTHS	72"
TRIM CAPACITY	9.5" (both sides of mower)
TOTAL WEIGHT	72": 2,428 lbs.

Optional Accessories: Mulch Kit, Snow Blower, Snow Blade, Rotary Broom, Hard Cab, Soft Cab, Remote Hydraulic Kit, Light Kit (ROPs mounted), Beacon Kit (ROPs mounted), Flasher Kit (ROPs mounted), Heavy Duty Air Box

