



HUSTLER
ENGINEERING PERFORMANCE

SUPER Z[®]

- ▶ VX4[®] deck - clean cut, excellent performance in all conditions
- ▶ Simple design
- ▶ Grammer Suspension Seat
- ▶ Unmatched hydraulics - oil shuttle and cooler separates it from the competition
- ▶ 14 mph
- ▶ Standard, certified ROPS and seat belt

LIMITED
WARRANTY

2 YEAR | **NO** HOUR LIMIT **OR** **5** YEAR | **500** HOUR

See your local Hustler dealer for complete warranty details

LIMITED

LIFETIME WARRANTY

FRAME & LEADING EDGE OF THE DECK

AVAILABLE AT CERTIFIED DEALERS



SUPER Z

ENGINE

MANUFACTURER	Kawasaki, Kohler
HP	54", 60" deck: 27HP - FX850 72" deck: 35HP - FX1000 54", 60" deck: 29HP - Kohler 824 EFI 66", 72" deck: 33HP - Kohler 824 EFI * Per SAE J1995
DISPLACEMENT	FX850: 852cc FX1000: 999cc 824 EFI: 824cc
COOLING	Air Cooled
AIR CLEANER	Heavy Duty Canister
ENGINE WARRANTY	3 year

DRIVE SYSTEM

TYPE	Dual Hydrostatic
PUMPS	21cc HydroGear PY pumps
WHEEL MOTORS	Parker TG310
HYDRAULIC LINES	Stainless Steel Parker Seal Loc Technology
HYDRAULIC COOLING	Oil cooler w/ 8" fan
RESERVOIR CAPACITY	3 gal.
SPEED	14 mph
PARKING BRAKES	Patented automatic

DECKS

CUTTING WIDTH	Side: 54", 60", 66", 72" Rear: 60", 72"
CUTTING HEIGHTS	1" - 5.5"
DECK LIFT	Foot Operated
DEPTH	5.5"
BLADES	3
BLADE LENGTH	54" deck: 3 - 18.5" x 2.5" x .20" 60" deck: 3 - 20.5" x 3.0" x .25" 66" deck: 3 - 22.5" x 3.0" x .25" 72" deck: 3 - 24.5" x 3.0" x .25"
SPINDLES	Ductile cast iron w/ steel shafts and sealed ball bearings
DECK BELTS	1
DRIVE	Electric PTO Clutch

CONSTRUCTION	11ga. +11ga.+7ga. welded steel
SPINDLE MOUNTS	Reinforced 11ga. doubler +7ga. tripler, steel

IMPACT/TRIM AREAS	1.5" x .375" steel bar protector
-------------------	----------------------------------

CONSTRUCTION

FRAME	1.5" x 3.0" x .187" steel
FRONT CASTER WHEELS	Mounted w/ sealed ball bearings
FRONT CASTER FORKS	Fabricated 1/2" steel

GENERAL

SEAT	Bolstered Grammer susp. seat
FUEL CAPACITY	12 gal.
CUP HOLDER	Yes
FRONT TIRE	13 x 6.5 - 6
DRIVE TIRE	54" deck: 24 x 9.5 - 12 60", 66", 72" deck: 24 x 12 - 12

DIMENSIONS

WEIGHT	54": 1491 lbs 60": 1511 lbs 66": 1560 lbs 72": 1588 lbs
HEIGHT W/ ROPS UP	71.5"
HEIGHT W/ ROPS FOLDED	54"
LENGTH	54", 60" deck: 84.5" 66" deck: 85" 72" deck: 86.7"
WIDTH	54" deck: 60" w/ chute up 60" deck: 66" w/ chute up 66" deck: 72" w/ chute up 72" deck: 78" w/ chute up
TIRE WIDTH	54", 60" deck: 57" 66", 72" deck: 60"

PRODUCTIVITY*

ACRES PER HOUR	54": 6.11 60": 6.78 66": 7.46 72": 8.14
----------------	--

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

Optional Accessories: 3 Bag Grass Catcher (12 bu.), BacVac Grass Catcher (10 bu.) electric accuated dump, Mulch Kit, Lights, Semi Pneumatic front tires, FlexForks, Steering Extension Kit, Sand Kit, Deck Rear Anti-scalp wheels, Deck Stripe Kit, Hydraulic Deck Lift, Beacon Kit, Flasher Kit, Isolator Grammer Seat, High Vacuum Deck Kit

