

RAMROD

COMPACT MINI SKID LOADER SOLUTIONS



RAMROD MODEL 1350



MODEL 1330



MODEL 930



MODEL 500

For over 30 years, RAMROD has engineered and manufactured material handling solutions for construction, demolition, underground mining, fencing, agriculture, irrigation, and hundreds of other applications. With over 70 attachments the RAMROD product line can help benefit your business with compact, labour saving solutions. Call today or visit us online to discuss your needs!

1-800-667-5181

(306) 786-2600

sales@ramrodequip.com

www.RAMRODEQUIP.com

RAMROD FEATURES

- RAMROD's Exclusive, Patented "High-Torque" Hydraulic Drive System
- 3 Year Warranty
- 30 degree Bucket Rollback Angle
- Full 85 degree Dump Angle
- Greaseable Pivot Points
- Easy Single Hand Palm Steering
- Easy Serviceability
- High Machine Under Clearance
- SAFER, Self-levelling Loader Arms
- Powder Paint Finish
- All Day Fuel Tanks
- A Full 360 degree Operator Visibility
- Choice of Gasoline or Diesel Engines
- Exclusive RAMROD Rigid Track System
- Narrow Width
- Choice of Track or Wheels
- Over 70 Attachments Available
- Competitive Financing/Leasing Options

CALL US TODAY!

SPECIFICATIONS:

Tractive (Push-Pull) Capacity, lbs (kg)	1700 (771)
Lift Capacity, lbs (kg)	1350 (614)
Carrying Capacity, lbs (kg)	2700 (1227)
Lift Height (to hinge pin)	72" (183 cm)
Hydraulic Pump Capacity	7 to 14 GPM
Hydraulic Pumps	2
Track Size	9" (23 cm)
Self-Levelling Loaders Arms Standard	Yes
Body Height	51.5" (130.8 cm)
Length with bucket	86.4" (219 cm)
Ground Clearance	6.5" (17 cm)

RAMROD PRO SERIES 1350



SPECIFICATIONS:

Tractive (Push-Pull) Capacity, lbs (kg)	1450 (658)
Lift Capacity, lbs (kg)	1330 (604)
Carrying Capacity, lbs (kg)	2660 (1209)
Lift Height (to hinge pin)	72" (183 cm)
Hydraulic Pump Capacity	7 to 14 GPM
Hydraulic Pumps	2
Track Size	6" & 9"
Self-Levelling Loaders Arms Standard	Yes
Body Height	50.5" (128.3 cm)
Length with bucket	81.5" (207 cm)
Ground Clearance	6.5" (17 cm)

RAMROD PRO SERIES 1330



SPECIFICATIONS:

Tractive (Push-Pull) Capacity, lbs (kg)	1100 (499)
Lift Capacity, lbs (kg)	930 (422)
Carrying Capacity, lbs (kg)	2000 (907)
Lift Height (to hinge pin)	72" (183 cm)
Hydraulic Pump Capacity	0 to 11 GPM
Hydraulic Pumps	2
Self-Levelling Loaders Arms Standard	Yes
Body Height	50.5" (128.3 cm)
Length with bucket	81.5" (207 cm)
Ground Clearance	6.5" (17 cm)

RAMROD PRO SERIES 930



RAMROD ESTATE SERIES 575T & 500

SPECIFICATIONS:

	575T	500
Tractive (Push-Pull) Capacity, lbs (kg)	995 (452)	995 (452)
Lift Capacity, lbs (kg)	575 (262)	500 (227)
Carrying Capacity, lbs (kg)	975 (443)	825 (375)
Lift Height (to hinge pin)	66" (183 cm)	66" (183 cm)
Hydraulic Pump Capacity	0 to 6.3 GPM	0 to 6.3 GPM
Self-Levelling Loaders Arms Standard	Yes	Yes
Body Height	48.5" (123.2 cm)	48.5" (123.2 cm)
Length with bucket	77.5" (199.9 cm)	77.5" (199.9 cm)
Weight lbs (kg)	1380 (627)	1150 (500)
Ground Clearance	4.75" (12.07 cm)	4.75" (12.07 cm)

OVER 70 ATTACHMENTS TO CHOOSE FROM!

RAMROD WB1500 TX



SPECIFICATIONS:

Tractive (Push-Pull) Capacity, lbs (kg)	1200 (545)
Lift Capacity, lbs (kg)	1500 (680)
Carrying Capacity, lbs (kg)	2000+ (1000+)
Lift Height (to hinge pin)	66" (167.6 cm)
Hydraulic Pump Capacity	0 to 11 GPM
Hydraulic Pumps	2
Self-Levelling Loaders Arms Standard	Yes
Body Height	45.5" (115.6 cm)
Length with bucket	83.5" (212.1 cm)
Ground Clearance	5" (12.7 cm)

ASK ABOUT CUSTOM UNITS!

- ROOFER UNIT**
- DEMOLITION UNIT**
- REMOTE CONTROL OPTION**
- PROPANE OPTION**

