



QUICK SPECS

Weight	5,615 lbs
Horsepower	20.4 hp
Digging Depth	9'0"

Goes places bigger excavators can only dream about.

If you work on tight residential or inner city jobsites, you need an excavator that fits through narrow openings and works comfortably in tight quarters. Meet the new ViO25-6. This scrappy, go-almost-anywhere true zero tail swing excavator works anywhere you can fit the tracks. It also comes with a fuel-efficient 20.4-hp Final Tier 4 engine that delivers unexpected power for its size, with less environmental impact. We apologize if it gives those bigger excavators nightmares.



ViO25-6

POWERFUL, EFFICIENT ELECTRONICALLY CONTROLLED 20.4-HP FINAL TIER 4 DIESEL ENGINE

JOYSTICK PILOT CONTROLS WITH CONTROL PATTERN CHANGE STANDARD

AUXILIARY HYDRAULICS W/ PROPORTIONAL CONTROL STANDARD

2-SPEED DRIVE CONTROL STANDARD

OPTIONAL ENCLOSED CAB WITH HEAT

HYDRAULIC QUICK COUPLER

NEW DIGITAL SMART ASSIST CONTROL SYSTEM

QUICK SPECS

Model		ViO25-6	
Type		Canopy	Cabin
Operating Weight	Rubber Track	5615 lbs	5915 lbs
Engine	Type	Water-cooled 4-cycle Final Tier 4 Diesel	
	Model	3TNV80F-SXNBV	
	Rated Output	20.4 hp / 2500 RPM	
Performance	Max Digging Force, Bucket / Arm	5516 lbs / 2888 lbs	
	Traveling Speed, High / Low	2.9 MPH / 1.7 MPH	
	Rear Swing Radius	29.5 in.	
Working Area	Max Digging Height	13 ft. 7 in.	
	Max Digging Depth	9 ft. 0 in.	
	Max Digging Radius	15 ft. 5 in.	
Travel	Track Width	4 ft. 11 in.	
	Crawler Length	6 ft. 8 in.	
	Crawler Width	9.8 in.	
	Min. Ground Clearance	12.6 in.	
Capacity	Fuel Tank	8.1 gal	
	Hydraulic Oil Tank	6.6 gal	
Lifting Capacity	Over Front Blade Up	805 lbs	
	Over Front Blade Down	1153 lbs	
	Over Side Blade Up	672 lbs	

